

Microwave coaxial

Type: A 81 UFP



Engineering data

Cable design

Center conductor	silver-plated solid copper wire
Dielectric	ePTFE wrapped
Shield	silver-plated copper tape silver-plated braid
Jacket	FEP
Out-side diameter	Ø 7,9 mm
Weight	0,182 kg/m

Electrical data

Impedance	50 ohms
Capacitance	80 pF/m
Frequency range	DC – 18 GHz.
V.S.W.R.	<1,30
Insertion loss	see table 1
Velocity of propagation	84 %
Shielding effectiveness	< -100 dB/m typical

Mechanical and environmental data

Temperature range	-65 to +165°C
Salt spray	96 hours
Bending radius	80 mm (static) 120 mm (dynamic)





Table 1



© GigaLink Microwave Connection Engineering b.v. Subject to change without prior notice.

High Performance ultra low loss coaxial cable

Frequency range:
DC – 18 GHz.

Gigalink Microwave Connection Engineering B.V.

Albert Plesmanweg 39 T
3088 GB ROTTERDAM

Tel. +31 (0) 10 789 11 22
Fax. +31 (0) 10 789 11 44
E-mail: info@gigalink-mce.com

www.gigalink-mce.com

GTD-04-081-040402

This product is manufactured by Compagnie **Deutsch Bus & Microwave**.