

Microwave coaxial

Type: A 80 FP



Engineering data

Cable design

Center conductor	silver-plated flexible copper wire
Dielectric	ePTFE wrapped
Shield	silver-plated tape silver-plated braid
Jacket	FEP
Out-side diameter	Ø 8,0 mm
Weight	0,170 kg/m

Electrical data

Impedance	50 ohms
Capacitance	80 pF/m
Frequency range	DC – 18 GHz.
V.S.W.R.	<1,30
Insertion loss	see table 1
Velocity of propagation	80 %
Shielding effectiveness	< -100 dB/m typical

Mechanical and environmental data

Temperature range	-65 to +165°C
Salt spray	96 hours
Bending radius	45 mm (static) 80 mm (dynamic)
Flex life	>35.000





Table 1



© Gigalink Microwave Connection Engineering b.v. Subject to change without prior notice.

High Dynamic ultra low loss coaxial cable

Frequency range:
DC – 18 GHz.

Gigalink Microwave Connection Engineering B.V.

Albert Plesmanweg 39 T
3088 GB ROTTERDAM

Tel. +31 (0) 10 789 11 22
Fax. +31 (0) 10 789 11 44
E-mail: info@gigalink-mce.com

www.gigalink-mce.com

GTD-08-080-040402

This product is manufactured by Compagnie **Deutsch Bus & Microwave**.