

Microwave coaxial Type: A 150 P



Engineering data

Cable design

Center conductor	silver-plated solid copper wire
Dielectric	ePTFE wrapped
Shield	silver-plated tape silver-plated braid
Innerjacket	FEP
Reinforcement	Kapton® tape
Jacket	Polyurethane
Out-side diameter	Ø 19,0 mm
Weight	0,475 kg/m

Electrical data

Impedance	50 ohms
Capacitance	80 pF/m
Frequency range	DC – 8 GHz.
V.S.W.R.	<1,30
Insertion loss	see table 1
Velocity of propagation	80 %
Shielding effectiveness	< -100 dB/m typical

Mechanical and environmental data

Temperature range	-65 to +165°C
Salt spray	96 hours
Bending radius	180 mm (static) 250 mm (dynamic)
Flex life	>1.000





Table 1



© GigaLink Microwave Connection Engineering B.V. Subject to change without prior notice.

Field ultra low loss coaxial cable

Frequency range:
DC – 8 GHz.

Gigalink Microwave Connection Engineering B.V.

Albert Plesmanweg 39 T
3088 GB ROTTERDAM

Tel. +31 (0) 10 789 11 22
Fax. +31 (0) 10 789 11 44
E-mail: info@gigalink-mce.com

www.gigalink-mce.com

GTD-18-151-040402

This product is manufactured by Compagnie **Deutsch Bus & Microwave**.