

Microwave coaxial Type: A 60 PPP



Engineering data

Cable design

Center conductor	silver-plated solid copper wire
Dielectric	ePTFE wrapped
Shield	silver-plated tape silver-plated copper
First Innerjacket	FEP
Reinforcement	Kapton® tape
Second Innerjacket	Polyurethane
Reinforcement	Kapton® tape
Jacket	Polyurethane
Out-side diameter	Ø 13,2 mm
Weight	0,23 kg/m

Electrical data

Impedance	50 ohms
Capacitance	80 pF/m
Frequency range	DC – 26,5 GHz.
V.S.W.R.	<1,30
Insertion loss	see table 1
Velocity of propagation	84 %
Shielding effectiveness	< -100 dB/m typical

Mechanical and environmental data

Temperature range	-65 to +100°C
Bending radius	40 mm (static) 90 mm (dynamic)
Flex life	>1.000.





Table 1



© GigaLink Microwave Connection Engineering B.V. Subject to change without prior notice.

Shipboard ultra low loss coaxial cable

Frequency range:
DC – 26,5 GHz.

Gigalink Microwave Connection Engineering B.V.

Albert Plesmanweg 39 T
3088 GB ROTTERDAM

Tel. +31 (0) 10 789 11 22
Fax. +31 (0) 10 789 11 44
E-mail: info@gigalink-mce.com

www.gigalink-mce.com

GTD-21-061-040402

This product is manufactured by Compagnie **Deutsch Bus & Microwave**.